

netis®

Easy Network, Trustable

5 Port Fast Ethernet PoE Switch/ 4 Port PoE/802.3at/af

PE6105



Features:

- >5 10/100Mbps Auto-Negotiation RJ45 ports, 4PoE function
- >Supports PoE power up to 30W for each PoE port ,60W for all PoE ports
- >Supports PoE IEEE 802. 3at/af compliant Powered Device (PD)
- >IEEE 802.3x flow control for Full Duplex mode and backpressure for Half Duplex mode
- >1Gbps switching fabric capacity/backplane bandwidth
- >Supports 2K MAC address table, MAC address auto-learning & auto-aging
- >Green Ethernet technology for effective power saving
- >LED indicators for simple diagnostics and management
- >Plug and play ,no configuration required
- >Steel case, with external power supply

What it does:

The netis PE6105 Fast Ethernet PoE Switch provides a great selection for expanding your home or office network. It provides 5 10/100Mbps RJ45 ports , port 1 to port 4 support Power over Ethernet(PoE) function. It can automatically detect and supply power with the IEEE 802.3at/af compliant Powered Devices (PDs), like PoE APs, IP Phones, IP cameras, etc. In this case, the electrical power is transmitted along with data in one single cable allowing you to expand your network to where there are no power lines or outlets.

Specification:**Hardware**

Interface	5 10/100Mbps RJ45 port, 4 PoE function
LED	PWR, 1-5 LINK
Power Supply	48V
PoE Power	60W
Dimensions (L xW x H)	100x 100 x 26mm

Switching Features

Standards	IEEE 802.3u 100BASE –TX, IEEE 802.3 10BASE –T, IEEE 802.3at/af
Access Method	CSMA/CD
Transmission Method	Store and Forward
Switching Fabric Capacity	1Gbps
MAC Address Table	2K, auto-learning & auto-aging
PoE	30 Watts (Max. each port) 60 Watts (Max. all ports)

Others

Certification	FCC, CE	
Environment	Operating Temperature: 0°C~40°C Operating Humidity: 10%~90%RH non-condensing	Storage Temperature: -40°C~70°C Storage Humidity: 5%~90%RH non-condensing
Package	1*PE6105 1*Quick Installation Guide 1*Power Adapter 1*Power Cord	